Printing date 13.06.2019 Version number 1 Revision: 25.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Liquid Elements Clay Lube
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Lubricant for cleaning clay
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

AREA 52 GmbH

Thüngenfeld 4

D-58256 Ennepetal

Germany

tel. +49-(0)2333-3068945

e-mail: info@liquidelements.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: tel.: +49 (0)2333-3068945 (Monday to friday: 8:00 17:00)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information: Void
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PRT

The product does not contain any PBT (PBT: persistent, bioaccumulative, toxic) substance or does not fulfil criteria for PBT according to annex XIII of regulation (EC) 1907/2006 (< 0.1 %).

· vPvB:

The product does not contain any vPvB (vPvB: very persistent, very bioaccumulative) substance or does not fulfil criteria for vPvB according to annex XIII of regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 111-76-2	2-butoxyethanol	1-<3%
EINECS: 203-905-0 Index number: 603-014-00-0	•• Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
Reg.nr.: 01-2119475108-36	5 17.0 2, 110.10, 2,ye 17.0 2, 110.17	
CAS: 147170-44-3	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-	1-<3%
EC number: 931-333-8	(C8-18 and C18-unsatd. acyl) derivs., inner salts	
Reg.nr.: 01-2119489410-39		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

– EU

Printing date 13.06.2019 Version number 1 Revision: 25.02.2019

Trade name: Liquid Elements Clay Lube

(Contd. of page 1)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: If symptoms persist consult doctor.
- · After inhalation: Fresh air. If pain persists, get medical attention.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Immediately flush eyes with plenty of water with lids lifted. If symptons persist, seek medical advice.

· After swallowing:

Rinse out mouth and drink plenty of water.

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Full water jet
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Mouth respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Ensure adequate ventilation

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Observe the usual precautionary measures for handling chemicals.

Avoid contact with eyes.

Avoid close or long term contact with the skin.

· Information about fire - and explosion protection: No special measures required.

(Contd. on page 3)

Printing date 13.06.2019 Version number 1 Revision: 25.02.2019

Trade name: Liquid Elements Clay Lube

(Contd. of page 2)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store in dry conditions at 10 25 °C.
- · Storage class: 10 13 (Germany)
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

IOELV Short-term value: 246 mg/m³, 50 ppm Long-term value: 98 mg/m³, 20 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Observe the usual precautionary measures for handling chemicals.

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves according EN 374.

Check the permeability prior to each anewed use of the glove.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.5 \text{ mm}$

Penetration time: ≥ 480 *minutes (Permeation according to EN 374 Part 3: Level 6)*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.11 mm

- · Eye protection: Goggles recommended during refilling
- · Body protection: Light weight protective clothing

Printing date 13.06.2019 Version number 1 Revision: 25.02.2019

Trade name: Liquid Elements Clay Lube

(Contd. of page 3)

	(Cond. of pa
SECTION 9: Physical and chemic	cal properties
9.1 Information on basic physical and cl	hemical properties
General Information	1 1
Appearance:	
Form:	Liquid
Colour:	Green
Odour:	Perfumed
Odour threshold:	Not determined.
pH-value at 20 °C:	~ 7
Change in condition	
Melting point/freezing point:	Not determined.
Initial boiling point and boiling range:	: 100 °C
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Oxidising properties	Not applicable.
Vapour pressure:	Not determined.
Density at 20 °C:	$\sim 1.0 \text{ g/cm}^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Easily soluble.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	< 3 %
Solids content:	< 3 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

Printing date 13.06.2019 Version number 1 Revision: 25.02.2019

Trade name: Liquid Elements Clay Lube

(Contd. of page 4)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
111-76-2 2-butoxyethanol			
Oral	LD50	1,480 mg/kg (rat)	
Dermal	<i>LD50</i>	1,060 mg/kg (rabbit)	
Inhalative	LC50/8 h	$10-20 \text{ mg/m}^3 \text{ (rat)}$	
147170-44-3 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd.			
acyl) derivs., inner salts			
Oral	<i>LD50</i>	>5,000 mg/kg (rat) (OECD 401)	
Dermal	<i>LD50</i>	>2,000 mg/kg (rat) (OECD 402)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity: 111-76-2 2-butoxyethanol EC50 911 mg/l (algae) (72 h) 1,550 mg/l (daphnia magna) (48 h) LC50 >100-1,700 mg/l (fish)

147170-44-3 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd. acyl) derivs., inner salts

EC50 >1-10 mg/l (algae) (OECD 201) LC50 >1-10 mg/l (fish) (OECD 203)

- · 12.2 Persistence and degradability The solvent is biodegradable
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 6)

Printing date 13.06.2019 Version number 1 Revision: 25.02.2019

Trade name: Liquid Elements Clay Lube

(Contd. of page 5)

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Smaller quantities can be disposed of with household waste.

Dispose of in accordance with all applicable local and national regulations.

· European waste catalogue

20 01 30 detergents other than those mentioned in 20 01 29

15 01 02 plastic packaging

- · Uncleaned packaging:
- · Recommendation:

Dispose of in accordance with all applicable local and national regulations.

Non contaminated packagings may be recycled.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

· 14.1 UN-Number	
· ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Anne Marpol and the IBC Code	x II of Not applicable.
· Transport/Additional information:	Product with comparable composition does not suppo- combustion according to method L.2 (sustaine combustibility test).
· UN ''Model Regulation'':	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed, if applicable.

(Contd. on page 7)

Printing date 13.06.2019 Version number 1 Revision: 25.02.2019

Trade name: Liquid Elements Clay Lube

(Contd. of page 6)

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out, because it is not necessary for mixtures.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS:

Chemisches Labor & Consulting - Dr. Ulrich Bönig

Simonshöfchen 55, D-42327 Wuppertal

Germany

Tel.: +49-(0)202-7387557

· Contact: Mr. Boenig, PhD.

· Abbreviations and acronyms: CLP: Classification, Labelling and Packaging (Regulation (EC) No. 1272/2008

REACH: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.

EC50: effective concentration, 50 percent

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

VCI: Verband der chemischen Industrie, Deutschland (German chemical industry association)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

 $A quatic\ Chronic\ 3:\ Hazardous\ to\ the\ aquatic\ environment\ -\ long\ -term\ aquatic\ hazard\ -\ Category\ 3$